


FRAME ORDER FORM

					ORDER DATE: _____					P.O. #: _____							
					SOLD TO: NAME _____ ADDRESS _____ CITY _____ ST. _____ ZIP _____ CONTACT _____ PHONE _____ FAX _____					SHIP TO: NAME _____ ADDRESS _____ CITY, ST, ZIP _____ CONTACT _____ PHONE _____							
MODULEX BILL OF MATERIALS	ELEV. NO.	QTY.	WALL SIZE <small>(inches)x(fract)</small>	FINISH	Fire Rating	DOOR SIZE WIDTH X HEIGHT <small>(feet/inches)x(feet/inches)</small>			GLAZING SIZE I.D.WIDTH X I.D. HEIGHT <small>(feet/inches)x(feet/inches)</small> (ATTACH DRAWING)			TRIM STYLE	PRE- MORTISE HANDING <small>(CHART REQ)</small>	STRIKE PREP.	HINGE PREP	CUT	MARK NUMBERS
NOTES:																	

INSTRUCTIONS:

1. ELEV. - Drawing elevation number for reference.
2. QTY. - Quantity of line item ordered.
3. WALL SIZE - Use one of the following choices:
3-3/4, 4-7/8, 5-1/4, 7-1/4
4. FINISH - Use one of the following choices:
CLEAR (anodized)
BRONZE (anodized)
5. FIRE RATING - Specify 20 Min Neg or Pos Pressure. Will be Non Rated if not noted.
6. DOOR SIZE - Standard / nominal door call out size.
7. GLAZING SIZE - Inside dimension of finished glazing opening.

ATTACH DRAWINGS OF ALL GLAZING UNITS!!!


8. TRIM STYLE
1", 1 1/2", 2"
9. PREMORTISE HANDING - Use one of the following:
SMR - Non-handed for field mortising.
RH - Butt-to-butt right hand swing.
LH - Butt-to-butt left hand swing.
RHR - Butt-to-butt right hand reverse swing.
LHR - Butt-to-butt left hand reverse swing.
PAIR - Pair of doors.

10. STRIKE PREP. - Use one of the following choices:
SP234 - 2 3/4" snap in strike plate for cylindrical locks.
ASA - Backer for standard ASA lock mfg. strike plate.
11. HINGE PREP. - Use one of the following choices:
PER DOOR LEAF - 5/16" DOOR BACKSET REQUIRED!!!!
345 - 3 each 4 1/2" standard template hinge (.134 thickness)
445 - 4 each 4 1/2" standard template hinge (.134 thickness)
12. CUT - Place an "X" for material CUT NET in height.(No Scribe).
If not marked, material will be provided with 1" Scribe.
13. MARK NUMBER - I.D. number to appear on item box label.

SUPPLY HARDWARE LOCATIONS or Provide Manufacturer Location Name

HARDWARE LOCATION	From inside top of frame; to top of each hinge and centerline of strike plate				
CHART	1st Hinge	2nd Hinge	3rd Hinge	4th Hinge	Centerline Strike Plate

FRAME ORDER FORM

					ORDER DATE: _____					P.O. #: _____										
					SOLD TO: NAME _____ ADDRESS _____ CITY _____ ST. _____ ZIP _____ CONTACT _____ PHONE _____ FAX _____					SHIP TO: NAME _____ ADDRESS _____ CITY, ST, ZIP _____ CONTACT _____ PHONE _____										
MODULEX BILL OF MATERIALS	ELEV. NO.	QTY.	WALL SIZE (inches)x(fract)		FINISH	Fire Rating	DOOR SIZE WIDTH X HEIGHT (feet/inches)x(feet/inches)				GLAZING SIZE I.D.WIDTH X I.D. HEIGHT (feet/inches)x(feet/inches) (ATTACH DRAWING)				TRIM STYLE	PRE-MORTISE HANDLING (CHART REQ)	STRIKE PREP.	HINGE PREP	CUT	MARK NUMBERS
Modulex Use Only	A	3	4	7/8	Clear	20 Min	3	0	8	0	1	6	8	0	1 1/2"	SMR	SP234	445	X	1, 2, 3
	Sample																			
NOTES:																				

INSTRUCTIONS:

- 1. ELEV. - Drawing elevation number for reference.
- 2. QTY. - Quantity of line item ordered.
- 3. WALL SIZE - Use one of the following choices:
3 0/0, 3 1/4, 3 1/2, 3 3/4, 4 5/8, 4 7/8, 5 1/4, 5 3/8, 5 5/8, 6 1/4, 6 7/8, 7 1/4
- 4. FINISH - Use one of the following choices:
CLEAR (anodized)
BRONZE (anodized)

Paint Discontinued

- 5. FIRE RATING - Specity 20 Min Neg or Pos Pressure. Will be Non Rated if not noted.
- 6. DOOR SIZE - Standard / nominal door call out size.
- 7. GLAZING SIZE - Inside dimension of finished glazing opening.

ATTACH DRAWINGS OF ALL GLAZING UNITS!!!

- 8. TRIM STYLE
1", 1 1/2", 2"
- 9. PREMORTISE HANDLING - Use one of the following:
SMR - Non-handed for field mortising.
RH - Butt-to-butt right hand swing.
LH - Butt-to-butt left hand swing.
RHR - Butt-to-butt right hand reverse swing.
LHR - Butt-to-butt left hand reverse swing.
PAIR - Pair of doors.

- 10. STRIKE PREP. - Use one of the following choices:
SP234 - 2 3/4" snap in strike plate for cylindrical locks.
ASA - Backer for standard ASA lock mfg. strike plate.
- 11. HINGE PREP. - Use one of the following choices:
PER DOOR LEAF - 5/16" DOOR BACKSET REQUIRED!!!!
345 - 3 each 4 1/2" standard template hinge (.134 thickness)
445 - 4 each 4 1/2" standard template hinge (.134 thickness)
- 12. CUT - Place an "X" for material CUT NET height.(No Scribe).
If not marked, material will be provided with 1" Scribe.
- 13. MARK NUMBER - I.D. number to appear on item box label.

SUPPLY HARDWARE LOCATIONS or Provide Manufacturer Location Name

HARDWARE LOCATION CHART	From inside top of frame; to top of each hinge and centerline of strike plate				
1st	2nd	3rd	4th	Centerline	
Hinge	Hinge	Hinge	Hinge	Strike Plate	